

NKL-F-xxxM2MT-01B-BK

NIKOLAN Fiber-Optic Cable, Multimode 50/125 OM2, Multi Loose Tube Outdoor, With corrugated steel tape, Black



NIKOLAN cables, with corrugated steel tape are designed for laying in the cable sewerage, blocks, tunnels, collectors, on bridges and flyovers, in ground of 1-3 groups, between buildings and structures. NKL-F-xxxM2MT-01B-BK cables are designed for outdoor installation and contain twenty four, thirty six, forty eight or seventy two optical fibers comply with the following standard: ITU-T G652.D., ISO/ IEC 11801 OS2/OM2/OM3/OM4. Optical fibers are laid in the loose tube, which is filled with a hydrophobic gel. Optical modules are wrapped around a central strength member. Optical modules covered steel tape. The outer jacket is made of PE, resistant to ultraviolet radiation.

Ordering Table

P/N	Number of fibers	Fiber type	Jacket	Individual package	
				Volume, m3	Weight, kg
NKL-F-036M2MT-01B-BK36		MM 50/125 OM2	PE	-	-
NKL-F-048M2MT-01B-BK48		MM 50/125 OM2	PE	-	-
NKL-F-096M2MT-01B-BK96		MM 50/125 OM2	PE	-	-

NKL-F-xxxM2MT-01B-BK

NIKOLAN Fiber-Optic Cable, Multimode 50/125 OM2, Multi Loose Tube Outdoor, With corrugated steel tape, Black

Detailed characteristics

Characteristic	Value
CPR Class	Fca
Outer jacket material	PE
Application	Outdoor
Mass density (kg) per unit length (km)	91.0 kg/km / 91.0 kg/km / 145.0 kg/km
Maximum tensile strength	1000 N
Warranty	Component - 5 years. 25 years - as part of a certified NIKOMAX SCS
Packaging	Wooden drum
Diameter of cable	9.1 mm / 9.5 mm / 12.0 mm
Temperature ranges	Transportation and storage from -50 to +70 ° C. Laying and installation from -20 to +60 ° C. Operation -40 to +60 ° C
Compliance	ISO/IEC 11801 OM2 & ITU-T G.652.D
Number of fibers	36 / 48 / 96
Type of optical fiber	Multimode 50/125
Minimum bending radius	Not less than 20 times the cable diameter
Peripheral strength element	Steel rope
Color of outer jacket	Black