

## NMC-CC110UD5-100

110 type connector, 5 pairs



110 type connectors are designed to be used with 110 blocks. Connectors are installed on one side of the 110 block after wiring individual pairs of a horizontal or trunk cable on them, and the other side of the connector acts as a female part of a 110-type connector and is intended for connecting patch cords and jumpers. Also connectors can interconnect two cable segments, if used as a consolidation point. For sealing 110 panels, blocks and connectors, it is recommended to use the NMC-315DR tool for simultaneous sealing of several pairs (4 or 5, depending on the nozzle). It greatly facilitates and speeds up work.

### Ordering Table

P/N	Category	Number of pairs	Individual packaging			Transport packaging		
			Quantity	Volume, m3	Weight, kg	Quantity	Dimensions, mm	Weight, kg
NMC-CC110UD5e		5	100 pcs	0.0012	0.590	32 packs	515x395x230	20.02

## Detailed characteristics

Characteristic	Value
Warranty	Extended - 15 years. 25 years - as part of the certified NIKOMAX SCS
Packaging	Plastic bag, 100 pcs
Number of pairs	5
Category	5e
Bandwidth	100 MHz
IDC Type Contact	110
Installation	Fits 110 blocks and panels
Plastic material	Conforms to UL 94V-0
Color	White
Compliance	Exceeds the requirements of standards: ISO/IEC 11801, EN 50173 and TIA/EIA-568
Supported applications	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive
Temperature ranges	Storage from -40 to +70 °C. Installation from 0 to +50 °C. Operation from -10 to +60 °C