



Cable tester with LCD Display



Cable tester NIKOMAX NMC-TED400TR with LCD display is designed to work with a wide range of cables. These are UTP / STP cables twisted pair, terminated with RJ45 connectors, coaxial cables with BNC connectors, telephone cables RJ11 / RJ12, USB cables (type A - type B). The tester is able to diagnose such errors in the line as a violation of the wiring layout of conductors, breakage of conductors and short circuits, is able to measure the length of the cable line, as well as equipped with a trace function, with which you can find the desired cable in a bundle suitable for finding hidden wiring. Cable tester NIKOMAX with LCD display, UTP / STP, RJ11, RJ12, RJ45, BNC, USB, with length measurement function and cable routing The tester kit consists of a main module, a remote unit and a cable probe detector for testing.

Ordering Table

| P/N | Description | Individual package | | |
|--------------|-----------------------------|--------------------|------------|------------|
| | | Dimensions, mm | Volume, m3 | Weight, kg |
| | UTP / STP (USB, TEL, COA) | () | | |
| NMC-TED400TR | LAN tester with LCD display | 135 x 265 x 80 | 0.0028 | 0.569 |
| | and cable routing function | | | |



NMC-TED400TR

Cable tester with LCD Display

Detailed characteristics

| Characteristic | Value | | |
|--|--|--|--|
| Warranty | 1 year | | |
| Protection level | The main and remote module is gray | | |
| Housing material | Plastic | | |
| Packaging | Cardboard box | | |
| Temperature range | Storage from - 10 C to + 60 C, operation from - 10 C to + 60 C | | |
| Adjust screen contrast | Yes | | |
| Connectors on the device | 2 x RJ45 (main and scan), BNC, RJ11, USB type B | | |
| Line testing for breaks and short-circuits | Yes | | |
| Checking for correct wiring | Yes | | |
| Shielding integrity check | Yes | | |
| Battery | Battery type "Krona" (6LR61) | | |
| Type of cable | LAN UTP / STP, Tel. RJ11 / RJ12, Coax (BNC), UCB (type A-type B) | | |
| Cable trace | Yes | | |
| The choice of units of length | Yes, meters / feet / yards | | |
| Setting screen auto-off | Yes | | |
| Cable length measurement | Yes, up to 1000 meters | | |
| Calibration | Yes, storage up to 7 values | | |
| Setting the auto-off tester | Yes, 15 / 30 / 60 / 120 minutes | | |
| Intercom system | Yes | | |
| Maximum length of tested lines | 1000 m | | |