


NMF-CJ12S2PA-MTPM-LCU-1S

Pre-terminated optical cassette module, 12 ports LC / UPC, SM 9/125, OS2, available on request



Cassette modules are designed exclusively for mounting in NIKOMAX NMC-RP08-BLANK-CJ-1U-MT patch panel.

Optical cassettes are made in plastic translucent casings and as ready-made pre-terminated solutions with a capacity of 12 LC or SC ports. Inside the cassette there is a cable assembly of Hydra fan-out: 1x MTP-male (Premium) on 12x SC or LC connectors.

Ordering Table

P/N	Size, slot	Fiber type	Outgoing connectors		Weight, kg
			Quantity	Type/polish	
NMF-CJ12S2PA-MTPM-L1		SM 9/125 OS2	12	LC / UPC	0.14

NMF-CJ12S2PA-MTPM-LCU-1S

Pre-terminated optical cassette module, 12 ports LC / UPC, SM 9/125, OS2, available on request

Detailed characteristics

Characteristic	Value
Warranty	1 year
Packaging	Cardboard box
Type of optical fiber	Single Mode Fiber 9/125 (Single Mode)
Class of fiber	OS2 / G.652.D
Insertion loss	≤ 0.25 dB - for LC connector ≤ 0.1 dB - for MTP connector
Return loss	≥ 60 dB - for LC connector ≥ 60 dB - for MTP connector
Number of Front Ports	12
The ports are front. / Polishing	LC / UPC
Cassette size, slot	1
Port rear / polished	MTP Premium - Male / APC
Polarization	Type A
Jacket Casing Material	LSZH
Diameter of the cords	0.9 mm
Color of Fiber Optic cable shell	Blue, orange, green, brown, gray, white, red, black, yellow, purple, lilac, aqua
Cassette material	Plastic
Cassette color	Blue, translucent
Temperature range	Storage from -20 to +65 ° C. Operation -5 to +65 ° C