



NMF-PC2M3C2-SCU-LCU-xxx

Fiber Optic Patch Cord, MM 50/125 OM3, SC/UPC-LC/UPC, LSZH, Duplex

Ordering Table

P/N	Connection style	Connector type	Polishing	Length, m	Individual packing	
					Volume, m3	Weight, kg
NMF-PC2M3C2-SCU-Duplex		SC-LC	UPC	2	0.000210	0.030
NMF-PC2M3C2-SCU-Duplex		SC-LC	UPC	3	0.000210	0.040
NMF-PC2M3C2-SCU-Duplex		SC-LC	UPC	5	0.000210	0.050

NMF-PC2M3C2-SCU-LCU-xxx

Fiber Optic Patch Cord, MM 50/125 OM3, SC/UPC-LC/UPC, LSZH, Duplex

Detailed characteristics

Characteristic	Value
Outer jacket material	LSZH
Temperature ranges	Storage from -20 to +65 ° C. Operation -5 to +65 ° C
Warranty	1 year
Packaging	Plastic bag
Type of optical fiber	Multimode 50/125
Type of cable	Patch Cord
Class of fiber	ISO/IEC 11801 OM3
Connectors / Polishing	SC/UPC - LC/UPC
Diameter of outer jacket, mm	2
Color of outer jacket	Aqua
Insertion loss	≤ 0.3 dB
Return loss	≥ 50 dB