



NMF-PT1M3C0-LCU-xxx-001-2

Fiber Optic Patch Cord (Pigtail), MM, 50/125, OM3, LC/UPC-Empty

Fiber optic patch cords (pigtails) are designed to connect fiber optic cable to active network switches and patch panels by fusion splicing.

Fiber Optic Pigtails are manufactured with either multimode or single-mode fiber and terminated only on one side by SC, LC, FC, ST connector type and polished UPC or APC in a diameter of 0.9 mm and tight buffered outer jacket. Outer jacket is color coded to differentiate multimode or single-mode.

Ordering Table

P/N	Connector type	Polishing	Length, m	Individual packing	
				Volume, m3	Weight, kg
NMF-PT1M3C0-LCU-XXLC		UPC	1	0.000225	0.011

NMF-PT1M3C0-LCU-xxx-001-2

Fiber Optic Patch Cord (Pigtail), MM, 50/125, OM3, LC/UPC-Empty

Detailed characteristics

Characteristic	Value
Outer jacket material	LSZH
Warranty	1 year
Packaging	Plastic bag
Temperature ranges	Storage from -20 to +65 ° C. Operation -20 to +65 ° C
Type of optical fiber	Multimode 50/125
Type of cable	Patch Cord (Pigtail)
Connector type / polishing	LC/UPC
Class of fiber	ISO/IEC 11801, OM3
Diameter of outer jacket, mm	0.9
Color of outer jacket	Aqua
Insertion loss	≤ 0.3 dB
Return loss	≥ 50 dB