

NMF-SC-3V-48-6MS



Splice Closure, 48 fibers, 6 round ports, with 4 pcs. of splice tray, with standard accessories, mechanical sealing

Optical splice closure NMF-SC-3V-48-6MS is designed for use under any conditions of laying fiber-optic cable (overhead, on a support, in the ground, in cable ducts or cable wells).

The splice closure provide trunk splicing of optical cables, protection a place of welding, transit passage of optical modules and output optical line for the end user.

The housing of the splice closure is made of impact-resistant frost-resistant polycarbonate, provides long-term and reliable protection of intergrowths.

The cable entries are sealed with three gaskets of various materials and sealing tape, then tightened with a special nut. This solution provides moisture and dust insulation of cable entries without the use of heat shrinkers, hair dryers, and other heating equipment.

Ordering Table

P/N	Number of cable entries	Max. Cable diameter	Volume with packaging	Weight with packaging
NMF-SC-3V-48-6MS	6 round inputs	2 x 13 mm / 2 x 16 mm / 2 x 20 mm	-	-

Splice Closure, 48 fibers, 6 round ports, with 4 pcs. of splice tray, with standard accessories,
mechanical sealing

Detailed characteristics

Characteristic	Value
Packaging	Individual - Cardboard Box
Temperature range	Operation from - 50 C to + 70 C
Protection level	IP65
Dimensions (LxWxH), mm	295 x 202 x 81 mm
Maximum cable diameter	2 x 13 mm / 2 x 16 mm / 2 x 20 mm
Weight, kg	1.8 kg
Maximum number of splices	48
Number of cable entries	6 round inputs