



NMF-SC-4V-48-4HS

Splice Closure, 48 fibers, 3 round & 1 oval port, with 4 pcs. of splice tray, with standard accessories, thermo-sealing, shortened

Optical splice closure NMF-SC-4V-48-4HS is designed to be fixed on the supports of overhead cable lines, walls of buildings and structures. It is advantageous to use small capacitance couplings in places of branching peripheral communication lines and in places of branches of peripheral lines to subscriber lines. Recommended for places with high humidity and high content of dust in the air.

The "hot" method of assembling and sealing cable glands with heat shrinkable tubing increases the strength of the cable fixation system, the anti-vandal resistance of the coupling and ensures absolute isolation from dust and moisture. The body is made of impact-resistant frost-resistant polycarbonate.

Ordering Table

| P/N | Number of cable entries | Max. Cable diameter | Volume with packaging | Weight with packaging |
|------------------|-------------------------|-----------------------|-----------------------|-----------------------|
| NMF-SC-4V-48-4HS | 3 round & 1 oval | 4 x 20 mm / 1 x 40 mm | - | - |

NMF-SC-4V-48-4HS

Splice Closure, 48 fibers, 3 round & 1 oval port, with 4 pcs. of splice tray, with standard accessories, thermo-sealing, shortened

Detailed characteristics

| Characteristic | Value |
|---------------------------|---------------------------------|
| Packaging | Individual - Cardboard Box |
| Temperature range | Operation from - 50 C to + 70 C |
| Dimensions (L x W) | 288 x Ø178 mm |
| Protection level | IP68 |
| Maximum cable diameter | 3 x 12 mm / 1 x 13 mm |
| Weight, kg | 1.6 kg |
| Maximum number of splices | 48 |
| Number of cable entries | 3 round & 1 oval inlet/outlet |